

智能平面围边机 GOA-300U-SFG



Intelligent Flat Edge Banding Machine GOA-300U-SFG



适用范围

用于床垫面料与侧面围边料之间的缝合。

机器特点

- 本设备是一款自动输送床垫面料、输送带辅助转角的高速平面围边机。
- 采用300UB5无梭缝纫机头，也可定制百福机头。
- 厚重及大尺寸产品缝制时，输送带同时辅助机头同步送料，自动转角，减少了机头的负载，延长机头的使用寿命。
- 操作简单，省去了培训时间，大大提高了工作效率，确保产品的一致性。

机器参数 Parameters

常规包边带尺寸: Standard Banding Width:	38/40/42MM (其他尺寸可定制) 38/40/42 mm (customizable)	压脚提升高度: Presser Foot Lift Height:	12 mm
车缝厚度: Max. Sewing Thickness:	压缩后≤5MM ≤5 mm (after compression)	针距: Stitch Length:	≤7.6MM可调 Adjustable, ≤7.6 mm
最高转速: Max. Speed:	2500 RPM	工作台尺寸: Worktable Size:	4100 × 2000 mm
机器尺寸: Machine Dimensions:	4100 × 2940 × 1700 mm	包装尺寸: Packaging Dimensions:	4300 × 2150 × 1330 mm × 1; 1240 × 740 × 1650 mm × 1
净/毛重: Net/Gross Weight:	1000/1200 kg	气压: Air Pressure:	0.8 MPa
功率: Power:	2.6 kW	电压: Voltage:	三相380V, 50HZ 3-Phase 380V, 50Hz

Application

Specially designed for sewing mattress top panels to side border banding materials.

Features

- Automatic Feeding System – Equipped with conveyor belt-assisted corner turning for high-speed flat edge banding.
- Standard 300UB5 chainstitch sewing head, optional with Pfaff head as customization.
- Heavy-Duty Performance – Conveyor belt synchronizes with the sewing head for seamless fabric feeding and automatic corner turning, reducing head load and extending service lifetime.
- User-Friendly Operation – Minimal training required, ensuring high efficiency and consistent output quality.

天津再登高智能制造有限公司

地址: 天津宝坻经济开发区天宝南环路3号B楼-2号

邮箱: sales@raiseagaintech.com

网址: www.raiseagaintech.cn **400-166-8581**

Tianjin RaiseAgain SM CO., Ltd.

Address: No.2,Block B-3, Tianbao Nanhuan Road, Baodi Economic Development Area, Tianjin, China. **0086-22-6035 9933**

Email: sales@raiseagaintech.com

www.raiseagaintech.com