



激光雕刻切割机

Laser Engraving And Cutting Machine



图示型号 (Model): GOA-LC, NM-N-1-1300×900-C-SL-CGC80W-ZIH-1P220V

适用范围


适用于服装、家纺、家具、箱包、玩具、汽车内饰、制鞋等行业的非金属材料的切割和雕刻。





Application

Suitable for clothing, home textiles, furniture, luggage, toys, car interiors, shoemaking, and other industries cutting and carving of non-metallic materials in the industry.





机器特点

- •切割精度高,速度快。
- 软件支持激光光衰轨迹补偿, 切割路径优化;
- •切割中心可直接与 AutoCAD、CorelDraw、 AI、服装 CAD 等 软件无缝对接,操作便捷。
- 支持断电续雕, 工时预览, 动态实时显示加工轨迹和加工进度等。
- •设备通讯接口支持:以太网(10/100M), USB2.0,无线WIFI, U盘脱机读写文件。
- 支持多种图形格式: DXF, PLT, BMP, AI, DST, CDR, GIF, JPEG, PCX, TGA, TIFF等。

Features

- High cutting precision and fast cutting speed.
- The software supports laser power decay trajectory compensation and cutting path optimization.
- The cutting center can directly and seamlessly interface with software such as AutoCAD, CorelDraw, AI, and garment CAD, ensuring easy operation.
- It supports power-off resume carving, processing time preview, and dynamic real-time display of processing trajectory and progress, etc.
- The equipment supports communication interfaces including: Ethernet (10/100M), USB 2.0, wireless Wi-Fi, and offline file reading/writing via USB
- It supports multiple graphic formats: DXF, PLT, BMP, AI, DST, CDR, GIF, JPEG, PCX, TGA, TIFF, etc.





激光雕刻切割机 Laser Engraving And Cutting Machine

推荐型号 Recommend Models

推荐型号 Model	工作面积 Working Area	机器尺寸 Machine Size (L×W×H)
GOA-LC, NM-N-1-900×600-C-SL-CGC80W-ZIH-1P220V	900mm×600mm	1430mm×1100mm×1200mm
GOA-LC, NM-N-1-1200×600-C-SL-CGC80W-ZIH-1P220V	1200mm×600mm	1730mm×1100mm×1200mm
GOA-LC, NM-N-1-1300×900-C-SL-CGC80W-ZIH-1P220V	1300mm×900mm	1830mm×1400mm×1200mm
GOA-LC, NM-N-1-1500×900-C-SL-CGC80W-ZIH-1P220V	1500mm×900mm	2030mm×1400mm×1200mm
GOA-LC, NM-N-1-1600×1000-C-SL-CGC80W-ZIH-1P220V	1600mm×1000mm	2130mm×1500mm×1200mm

主要参数 Parameters

冷却方式: 水冷却 供电电源: AC220V/110V±10%, 50Hz Cooling Method: Water cooling Power Supply:

激光类型: 国产封离式CO2玻璃激光管

Laser Type: China Made sealed CO2 glass laser tube

标配: 激光专用冷水机,550W排烟机,微型空气压缩机

Standard Configuration: Laser-specific chiller, 550W exhaust fan, and Mini air compressor.

工作环境: 温度: 5~40℃ 湿度:5~80% 无凝水,无灰尘 或灰尘较少

Operating Environment: Temperature: 5~40 C, Humidity: 5~80% (Non-condensing), Dust-free or low-dust conditions

主要配置 Configurations




国产一线品牌,质量稳定, 工作时间长。

A first-tier domestic brand with stable quality and long working hours.



运动执行机构采用同步带模组,组装方便,便于后 期维护保养。具有使用寿命长;高速静音等优点。

The motion execution mechanism adopts a synchronous belt module, which is easy to assemble and facilitates later maintenance and upkeep. It features advantages such as long service life and high-speed silent operation.



蜂窝和方格两种规格形式的 工作平台

Honeycomb and grid types of work platforms.



激光切割机专用工业冷水机,具有超温报警,流量保护,水位保护等安全报警提示功能。温度控制精准,确保激光器的功率输出稳定。

The industrial chiller specially designed for laser cutting machines is equipped with safety alarm functions such as overtemperature alarm, flow protection, and water level protection. It enables precise temperature control to ensure stable power output of the laser.

天津再登高智能制造有限公司

地址: 天津宝坻经济开发区天宝南环路3号B楼-2号

邮箱: sales@raiseagaintech.com 400-166-8581 网址: www.raiseagaintech.cn

Tianjin RaiseAgain SM CO., Ltd.

Address: No.2,Block B-3, Tianbao Nanhuan Road, Baodi Economic Development Area, Tianjin, China. **0086-22-6035 9933**Email: sales@raiseagaintech.com www.raiseagaintech.com