


有梭多针电脑绗缝机 (飞梭-N型)



7#,10#飞梭
7#,10# shuttle



自动送棉装置 (选配)
Automatic fiber feeder (optional)

下载绗缝CAD软件
Download QuiltCAD



Download: https://d.getonagain.com/cn/CAD/package/GOA_Qui_V1_2025_06_10.exe

适用范围

适用于床笠, 床盖, 夏凉被, 绗缝被, 棉服等产品的花型绗缝。



Application

For quilting of fitted sheet, bed covers, summer quilts, quilts and clothing products with quilting pattern.

机器特点

- 电控系统: 15寸液晶显示屏, 简单易懂, 操作快捷, 可实时显示绗缝花样, 形象直观。
- 断线检测功能: 绗缝过程中, 当面线断线时, 机器暂停作业, 同时屏幕显示相关提示, 帮助工人快速分析错误所在。
- 断电保护功能: 如果在绗缝中途电源断开, 再接通电源可使花样在断电前的状态下继续进行作业。
- 统计功能: 自动存储一段时间内的工作信息, 可随时查询已绗缝产量和总产量。
- 可选配专业绗缝制版设计软件, 支持花样任意设计, 宜学宜用。

Features

- Computer Control System: 15-inch LCD screen, easy to understand, quick to operate, can display quilting patterns in real time, image intuitive.
- Thread Breakage Detection: When the upper thread is broken during quilting process, the machine operation is pause, and prompts the related message, to help worker quickly analyse where the problem is.
- Power Down Protection Function: If the power supply is interrupted during quilting, the system will resume operation of quilting pattern from the state it was in before the power down once the power is restored.
- Statistic Count Function: Automatic store the work information in a period of time, and provide the quilted quantity and total production anytime.
- Optional professional quilting pattern design software, freely design quilts pattern is possible, easy to learn and suitable for the application.

机器参数 Parameters

绗缝克重: Quilting Density:	≤600GSM	梭子: Shuttle Hook:	7#/10#	最高绗缝速度: Max. Quilting Speed:	800rpm
步长: Stitch Length:	2mm-7mm	绗缝厚度: Sewing Thickness:	≤25mm	电源: Voltage:	三相 380V 50Hz 3P 380V 50Hz

有梭多针电脑绗缝机 (飞梭-N型)



Computerized Multi-needle Shuttle Quilting Machine (Flying Shuttle-Model N)

推荐型号 Model

推荐型号 Model	针排数 Number of Needle Row	针排距 Needle Rows Spacing	X轴移动距离 Travel Distance in X-axis	绗缝宽度 Quilting Width	机器尺寸 Installation Area (L×W×H)	主轴转速 Quilting Speed (r/min)
GOA-QC-NM-LS2-64+64-203.2× 1600.2-1"RNS-SS7R-NA-3P380	2	76.2mm	203.2mm	1600mm	3850×1320×1800mm	600-800
GOA-QC-NM-LS3-64+64+64-203.2× 1600.2-1"RNS-SS10R-NA-3P380	3	76.2mm, 76.2mm, 152.4mm	203.2mm	1600mm	3850×1320×1800mm	600-800
GOA-QC-NM-LS2-94+94-305× 2362.2-1"RNS-SS10R-NA-3P380	2	76.2mm	305mm	2450mm	4650×1320×1800mm	550-750
GOA-QC-NM-LS3-94+94+94-305× 2362.2-1"RNS-SS10R-NA-3P380	3	76.2mm, 76.2mm, 152.4mm	305mm	2450mm	4650×1320×1800mm	550-750
GOA-QC-NM-LS3-128+128+128-305× 3225.8-1"RNS-SS10R-NA-3P380	3	76.2mm, 76.2mm, 152.4mm	305mm	3300mm	5550×1320×1830mm	450-650

包边绗缝被自动生产线 Automatic Tape Binding Quilt Production Line


单位/Unit: mm



机器选配 Optional Configuration



输送带裁切机
Conveyor Belt Cutting Machine



全自动包四边机
Automatic 4-Side Tape Binding Machine



收料架
Material Collecting Rack



全自动飞梭绕线机
Automatic Shuttle Winding Machine

天津再登高智能制造有限公司

地址: 天津宝坻经济开发区天宝南环路3号B楼-2号

邮箱: sales@raiseagaintech.com

网址: www.raiseagaintech.cn **400-166-8581**

Tianjin RaiseAgain SM CO., Ltd.

Address: No.2,Block B-3, Tianbao Nanhuan Road, Baodi Economic

Development Area, Tianjin, China. **0086-22-6035 9933**

Email: sales@raiseagaintech.com

www.raiseagaintech.com