

程控柱式双针旋转针杆综合 送料缝纫机 GOA-550-1780B



适用范围

适用于软件家居、汽车内饰等领域立体物料的花式线迹装饰明缝工序

机器特点

- 通过计算机控制缝纫机的正缝、倒缝、零针距和旋转针杆四类动作，通过排列组合缝制出各种花式线迹。
- 内置60余款单、双针常用花样，通过触摸屏选择即可切换花型，操作极其简便。
- 三同步综合送料结构，针杆在旋转过程中仍在摆动送料，确保缝制时送料平顺，上下层缝料不易产生移位。
- 配备瞬间调节内外压脚交替量、缝线张力快速切换、气动抬压脚、集成机头LED灯、免手缠绕线器、针距盘自锁等实用功能。
- 标配8MM针位，前置气动中分器。

主要参数 Parameters

送料方式: Feeding System:		交替压脚、送布牙和机针综合送料 Alternating Presser Foot, Feed Dog, and Needle Compound Feeding	
最高缝速: Max. Sewing Speed:	200 针/分钟 200 RPM	线芯直径: Bobbin Diameter:	φ 26mm
柱高: High Of The Post Bed:	160mm	最大针距: Max. Stitch Length:	9mm
最大抬压脚高度: Max. Presser Foot Lifting Height:	16mm	触摸控制屏: Touching Screen Control:	√
自动抬压脚: Pneumatic Auto Presser Foot Lifting:	√	DL功能: DL Function:	√
电压: Voltage:	AC 220V, 50HZ	功率: Power:	550W
		适用机针: Suitable Needle:	DPx17 18-23#
		最大内外压脚交替量: Max. Alternating Stroke of Inner and Outer Presser Feet:	6.5mm
		自动倒缝装置: Auto Back Tacking Device:	√
		操作空间: Operation Space:	335 x 260mm

Program Controlled Post-Bed Double-Needle Rotary Needle Bar Compound Feed Sewing Machine



Application

Suitable for decorative topstitching with fancy patterns on three-dimensional materials in industries such as upholstered furniture and automotive interiors.

Features

- A computer controlled the sewing machine performs forward & reverse stitching, zero stitch length, and rotary needle bar movements, all those 4 kinds of sewing. Through the combination of stitching process arrangement, can create various decorative stitch patterns.
- Includes over 60 commonly used single-needle and double-needle patterns. Patterns can be easily switched via a touch screen, making the operation extremely simple.
- Features a triple synchronous compound feed system. The needle bar continues to swing and feed during rotation, ensuring smooth feeding and preventing displacement between the upper and lower fabric layers.
- Equipped with instant adjustment for alternating presser foot height, quick tension switching, pneumatic presser foot lifting, integrated LED light on the machine head, a hands-free bobbin thread winder, and a self-locking stitch length dial, those practical features, etc.
- Standard 8mm needle position set, with a pneumatic front center split device.

天津再登高智能制造有限公司

地址: 天津宝坻经济开发区天宝南环路3号B楼
邮箱: sales@getonagain.com
网址: www.GetonAgain.com

400-166-8581

Tianjin GetonAgain SM Co., Ltd.

Address: Block B, No.3, Nan Huan Road, Economic Development Zone,
Baodi, Tianjin, China. **0086-22-6035 9933**
Email: sales@getonagain.com www.GetonAgain.com