

立体边缝纫机



机器特点

- 多工序合一，将嵌绳包边，两侧滚边绳缝合固定一次性完成，且自动拉料，无需人工辅助。
- 能突出显示线条轮廓部位，支撑性好。
- 双边对折包绳，绳子可用0-5mm直径范围，包边宽度可调节。

主要参数 Parameters

机器型号: Model:		GOA-IS,1404P-LTB	
立体带尺寸: 0-5cm; 0-6cm; 0-10cm可选 Stereo-band Size: 0-5cm; 0-6cm; 0-10cm optional		电压: Voltage:	AC 220V 50Hz
线迹: 链式线迹 Stitch Type: Chain stitch		功率: Power:	550w
最高转速: Max sewing Speed:	2500rpm	净重: Net Weight:	50kg
机针: Needle:	UO163 14#	毛重: Gross Weight:	70kg
压脚提升高度: Presser Foot Lift Stroke:	0-10mm	机器尺寸: Machine Size (L×W×H) :	1200mm×550mm×1300mm
针杆行程: Needle Bar Stroke:	0-34mm	包装尺寸: Machine Size (L×W×H) :	1230mm×655mm×1325mm


Stereo-edge Binding Sewing Machine

适用范围

枕头、立衬羽绒被、沙发、椅子、坐垫等的缝制。

Application

Edge-binding for pillows, baffle box duvets, sofas, chairs, cushions, etc.



Features

- Integrated with multi-procedures, edge wrapping with the decorative rope and both sides band folding and sewing can be done in one time, and automatic pulling, without manual assistance.
- High lighting the out line of the line with perfect 3D effect.
- Double-side edge-binding with rope wrapped, rope diameter between 0-5mm, and edge binding width adjustable.

天津再登高智能制造有限公司

地址: 天津宝坻经济开发区天宝南环路3号B楼-2号

邮箱: sales@raiseagaintech.com

网址: www.raiseagaintech.cn **400-166-8581**

Tianjin RaiseAgain SM CO., Ltd.

Address: No.2,Block B-3, Tianbao Nanhuan Road, Baodi Economic Development Area, Tianjin, China. **0086-22-6035 9933**

Email: sales@raiseagaintech.com

www.raiseagaintech.com