


预开松机

Pre-opener



机器特点

- 将称重开包机送过来的原料初步开松，通过送棉风机送到给棉机中；标配压棉装置；喂入长度与开包机数量有关。
- 机架采用Q235-A钢板焊接而成，经定性处理。
- 喂入帘为皮帘。
- 喂入罗拉为钢制沟槽形罗拉，直径φ110mm，上下对压结构。
- 开松辊为直径φ405mm无缝钢管配套高强梳针钉板，校准动平衡。
- 输棉风机独立传动，配套输棉风管，直径φ300mm；配桥型磁铁。
- 喂入由集棉箱光电控制，并设有正、反转倒顺开关。

Features

- Open and loose the raw fibers sent by the weighing bale opener and then sending to the feeder through blower; Standard configuration with fiber pressing device; The feeding length is related to the quantity of bale openers.
- Machine structure is welded by Q235-A steel, has been ageing treatment.
- Feeding conveyor lattice is leather type.
- Steel grooved feeding roller, 110mm diameter, with upper & lower pressing structure
- 405mm diameter opening roller is made by seamless steel rod provided with highly strong combing spiked bar, calibrated dynamic balance.
- Fiber-feed blowing fan is driven individually, matched with 300mm diameter fiber air-delivery pipe, equipped with a bridge type magnetic piece.
- Feeding is photoelectric control from the fiber collection box, equipped with forward and reverse movement on-off switch.

机器参数 Parameters

机幅宽度: Machine Width:	1300mm	辊筒直径: Roller Diameter:	φ450mm	输送帘速度: Conveyor Lattice Speed:	≤10m/min	产量: Output:	500kg/h
喂入长度：单台开包机：2500mm；双台开包机：4950mm Feeding Length: Single set bale opener: 2500mm; Double set bale opener: 4950mm							
主机功率：主电机7.5kW，喂入罗拉0.75kW，风机2.2kW Main Motor Power: Main motor 7.5kW, Feeding roller 0.75kW, Blower 2.2k							

天津再登高智能制造有限公司

地址：天津宝坻经济开发区天宝南环路3号B楼-2号

邮箱：sales@raiseagain.tech

网址：www.raiseagain.tech **400-166-8581**

Tianjin RaiseAgain SM CO., Ltd.

Address: No.2, Block B-3, Tianbao Nanhuan Road, Baodi Economic

Development Area, Tianjin, China. **0086-22-6035 9933**

Email: sales@raiseagain.tech

www.raiseagain.tech