


铺网机

Cross Lapper



机器特点

- 将梳理机输出的纤维网均匀折叠，铺至设定的宽度和厚度输送进下道工序。
- 机架主体采用Q235-A钢折板结构与型材撑挡组合而成。
- 斜帘为花纹帘，底帘和环帘为木帘，其余均为皮帘。
- 各帘传动辊用无缝钢管加工而成，轴头特殊加强结构。
- 铺网往复采用同步带（14M）传动，同步带轮为双搭子结构；往复传动电机配齿轮减速机。
- 铺网往复小车导网辊为不锈钢材料，直径φ160mm，链条传动，两端为尖锥形。
- 铺网机机架底脚配有膨胀螺丝固定孔。
- 底帘按钮点动调节高度。

Features

- Evenly folding and lapping the fiber webs from carding machine to the set width and thickness, then transferring to the next process.
- Machine frame main structure is made of Q235- A steel folded plate and profile support material.
- Slanted lattice conveyors are pattern embossed, the bottom lattice and ring lattice are wooden while the rest are leather made lattice.
- Each conveyors driving rollers are made of seamless steel pipes, with special enhanced shaft head.
- Web lapping reciprocating movement is driven by synchronous belt (14M), double-headed timing pulley structure, to-and-fro motor equipped with gear decelerator.
- Web lapping to-and-fro trolley guiding rollers are stainless steel material with 160mm diameter, chain driving and sharp tapered at two end side.
- Web lapping frame foot is equipped with expansion screw fixing holes.
- Bottom lattice conveyor height is adjusted by inching button.

机器参数 Parameters

输入帘宽度: Input Lattice Width:	2000mm	输出帘速度: 1-12m/min 可调 Conveyor Lattice Speed: 1-12m/min adjustable
输出帘宽度: Output Lattice Width:	3000mm	铺网帘速度: 20-40m/min 可调 Lapping Lattice Speed: 20-40m/min adjustable
配套功率: 上料电机1.5kW—2台, 升降电机1.5kW—2台, 往复电机3.7kW—1台, 底帘电机1.5kW—1台 Matching Power: Feeding motor 1.5kW - 2 sets, Lifting motor 1.5kW - 2 sets, Reciprocating motor 3.7kW - 1 set, Bottom lattice motor 1.5kW --1 set		

天津再登高智能制造有限公司

地址: 天津宝坻经济开发区天宝南环路3号B楼-2号

邮箱: sales@raiseagaintech.com

网址: www.raiseagaintech.cn **400-166-8581**

Tianjin RaiseAgain SM CO., Ltd.

Address: No.2,Block B-3, Tianbao Nanhuan Road, Baodi Economic Development Area, Tianjin, China. **0086-22-6035 9933**

Email: sales@raiseagaintech.com

www.raiseagaintech.com