

无胶棉烘箱

Thermal Bonding Oven



机器特点

- 对铺好的棉进行高温烘烤处理，让棉进行粘合固定。
- 控制采用变频，传动采用不锈钢网和帘棒。
- 烘房加热方式：加热管（电加热）。
- 热风循环穿透对流，上吹下吸；风道为抽屉式结构，便于拉出风道插板进行清理挂花，主要结构采用框架式（槽钢）冷板制作。

Features

- Heating the laid fibers at high temperature, set and bond the fibers well.
- Variable frequency control, transmission with stainless steel mesh and lattice conveyors.
- Heating method of the oven: electronic thermal tube.
- Hot air circulation penetrating convection, blowing on top and sucking at downside. Air duct is with drawer structure, convenient to pull out the duct inserts for cleaning residues. Machine structure is made from frame type steel beams with cold treatment.

机器参数 Parameters

保温板厚度： Thickness of Insulation Plate:	95mm	加热区域宽度： Heating Area Width:	2650mm	烘房加热方式：加热管（电加热） Oven Heating Method: Heating tube (electronic heating)
加热区域长度： Heating Area Length:	4m (3000mm) 6m (5000mm) 8m (7000mm) 10m (9000mm)			
烘房总功率： Total Power of Oven:	4m (52kW) 6m (72kW) 8m (92kW) 10m (112kW)			

天津再登高智能制造有限公司

地址：天津宝坻经济开发区天宝南环路3号B楼-2号

邮箱：sales@raiseagaintech.com

网址：www.raiseagaintech.cn **400-166-8581**

Tianjin RaiseAgain SM CO., Ltd.

Address: No.2, Block B-3, Tianbao Nanhuan Road, Baodi Economic Development Area, Tianjin, China. **0086-22-6035 9933**

Email: sales@raiseagaintech.com

www.raiseagaintech.com